



BANGLADESH OFFICE :
 HOUSE-16, ROAD- 13, BLOCK –G, NIKETON, GULSHAN -1 , DHAKA.
 BANGLADESH PHONE:+880 1 672993247 , EMAIL:
 irfan.af.bd@gmail.com

ZRST-270P-60

Electrical Characteristics

Model	270Wp	
Maximum Power at STC (Pmax)	270W±0-3%	
Optimum Operating Voltage(Vmp)	30V	
Optimum Operating Current(Imp)	9A	
Open-Circuit Voltage(Voc)	38.5V	
Short-Circuit Current(Isc)	9.33A	
Operating Temperature	-40°C to +85 °C	
Maximum System Voltage	1000Vdc(IEC) / 600 Vdc(UL)	
Maximum Series Fuse Rating	15A	
Power Tolerance	±3%	
	NOCT	47±2°C
Temperature Coefficient	Pmax	-0.47% / °C
	Voc	-0.346% / °C
	Isc	+0.036% / °C

STC: Irradiance 1000W/m² , Module Temperature 25°C , AM=1.5

Mechanical Characteristics

Cell Type	Polycrystalline (156mm)
Cell Arrangement	60(6*10)
Dimensions (LxWxH)	1640*992*40mm
Weight	16.5kgs
Front Glass	3.2 mm (0.13 inches) tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP65 rated
Wind Loads	2400 Pascal certified
Output Cables	Double insulated solar cable 4.0 mm ² (0.006 inches ²),symmetrical lengths (-) 900 mm (35.4 inches) and (+) 900 mm (35.4 inches), MC 4 or its compatible connectors

Quality and Warranty

- ◆ Rigorous quality control meets the highest international standard
- ◆ 5 years limited warranty on material and workmanship
- ◆ 25-year performance guarantee at 80% of the minimal rated power output
- ◆ 10-year performance guarantee at 90% of the minimal rated power output

Packing Configuration

Container	20"GP	40"GP	40"HC
Pieces Per Box			
Box Dimensions (LxWxH)			
Pieces Per Container			

Statement:

- Specifications are subject to change without further notifications
- Please read the product information, installation guide, quality warranty and any other related information

